



GENIUS LINE (GL) DOUBLE GARDEN GATE

The double garden gate is made of high quality material and is being used for gardens, swimming pools etc. The gate can be delivered in the following heights: 1000, 1250, 1500, 1800 en 2000 mm.

LEAF

The horizontal and vertical leaf tubes have the dimensions of 40x40x2 mm. Between the tubes a gauze mat is placed. The gauze mat has a mesh of 50 x 50 x 5 mm.

POSTS

The posts are made of round tubes ($\varnothing 60.3 \times 2$) and have a black cap. The post needs to be put in the ground for 800 mm.

LOCK

Stainless steel Locinox lock with europrofile cylinder and 3 keys.

GROUND BOLT

Optional an aluminium ground bolt for securing the leaf in an open position can be delivered.

PLACEMENT

In closed position an concrete, to place the ground bolt in, can be used. This is an option.

TURN DIRECTION

The leaf can be assembled to turn left or right.

CONNECTING MATERIAL

The connecting material and hinges are made out of stainless steel. If necessary black caps will be used.

SURFACE TREATMENT

Hot dip galvanised according NEN-EN-ISO 1461.

POWDER COATING

For an appealing and finishing touch an extra RAL coating layer can be put on. This will be done according NEN 5254. Standard colors are RAL 6005, RAL 6009 and RAL 9005, other colors are possible.

PRODUCT INFORMATION GARDEN GATES

TECHNICAL SPECIFICATIONS

GENIUS LINE	CLEAR OPENING	HEIGHT	LEAF TUBE	GAUZE MAT THICKNESS	GAUZE MAT MESH	C/C POSTS	POSTS	LOCK	GROUND BOLT	GROUND BLOCK
GL1010.10	2000	1000	40 x 40	5	50 x 50	2150	Ø 60.3	RVS	STANDAARD	OPTION
GL1010.12	2000	1250	40 x 40	5	50 x 50	2150	Ø 60.3	RVS	STANDAARD	OPTION
GL1010.15	2000	1500	40 x 40	5	50 x 50	2150	Ø 60.3	RVS	STANDAARD	OPTION
GL1010.18	2000	1800	40 x 40	5	50 x 50	2150	Ø 60.3	RVS	STANDAARD	OPTION
GL1010.20	2000	2000	40 x 40	5	50 x 50	2150	Ø 60.3	RVS	STANDAARD	OPTION
GL1212.10	2500	1000	40 x 40	5	50 x 50	2650	Ø 60.3	RVS	STANDAARD	OPTION
GL1212.12	2500	1250	40 x 40	5	50 x 50	2650	Ø 60.3	RVS	STANDAARD	OPTION
GL1212.15	2500	1500	40 x 40	5	50 x 50	2650	Ø 60.3	RVS	STANDAARD	OPTION
GL1212.18	2500	1800	40 x 40	5	50 x 50	2650	Ø 60.3	RVS	STANDAARD	OPTION
GL1212.20	2500	2000	40 x 40	5	50 x 50	2650	Ø 60.3	RVS	STANDAARD	OPTION
GL1515.10	3000	1000	40 x 40	5	50 x 50	3150	Ø 60.3	RVS	STANDAARD	OPTION
GL1515.12	3000	1250	40 x 40	5	50 x 50	3150	Ø 60.3	RVS	STANDAARD	OPTION
GL1515.15	3000	1500	40 x 40	5	50 x 50	3150	Ø 60.3	RVS	STANDAARD	OPTION
GL1515.18	3000	1800	40 x 40	5	50 x 50	3150	Ø 60.3	RVS	STANDAARD	OPTION
GL1515.20	3000	2000	40 x 40	5	50 x 50	3150	Ø 60.3	RVS	STANDAARD	OPTION
GL2020.10	4000	1000	40 x 40	5	50 x 50	4150	Ø 60.3	RVS	STANDAARD	OPTION
GL2020.12	4000	1250	40 x 40	5	50 x 50	4150	Ø 60.3	RVS	STANDAARD	OPTION
GL2020.15	4000	1500	40 x 40	5	50 x 50	4150	Ø 60.3	RVS	STANDAARD	OPTION
GL2020.18	4000	1800	40 x 40	5	50 x 50	4150	Ø 60.3	RVS	STANDAARD	OPTION
GL2020.20	4000	2000	40 x 40	5	50 x 50	4150	Ø 60.3	RVS	STANDAARD	OPTION

ALL SIZES IN MM