



CLASSIC LINE ARROW (CLA) TAIL END

The standard classic model. This type has an extra top rail. Between the two top rails rings have been placed. The palings have an arrow head on top. On one side a dragon tail has been placed.

FRAME

The frame has three sides of tubes of 50x25x2 mm. Between the horizontal tubes palings have been placed.

FRAME SLANTING

The frame can be delivered with a different angle.

PALINGS

Round tubes with a diameter of 26 mm are being used. The centre-to-centre is 150 mm, optional other c/c distances can be delivered.

RINGS

The rings have a diameter of 125 mm and are 6 mm thick.

POINTS BETWEEN PALINGS

Between the palings points can be assembled at the bottom. These points are made out of steel and have a diameter of 16 mm and is approximately 150 mm high. This is an extra protection again climbers.

GROUND ANCHORING

On one side the tail end can be delivered with an extended post or on a base plate. The post is 60 x 60 mm.

CONNECTING FENCING

The posts are being delivered with gauze peak connection. Optional strips of a weld mesh connection can be delivered.

SURFACE TREATMENT

Hot dip galvanised according NEN-EN-ISO 1461.

POWDER COATING

For an appealing and finishing touch an extra RAL coating layer can be put on. This will be done according NEN 5254.

TECHNICAL SPECIFICATIONS

CLASSIC LINE ARROW	WIDE	HEIGHT	FRAME	POSTS	PALINGS	C/C PALINGS	POINTS BETWEEN PALINGS Ø 16
CLA10.10	1000	1000	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLA10.12	1000	1250	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLA10.15	1000	1500	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLA10.18	1000	1800	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLA10.20	1000	2000	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLA10.25	1000	2500	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD

* STANDARD CUT TO A POINT
ALL SIZES IN MM

