



CLASSIC LINE PRO (CLP) TAIL END

This type is an extension on Classic Line and has three rails with which round palings are welded between the top and bottom rail. Between the two top rails rings have been placed. On one side a dragon tail has been placed.

FRAME	The frame has three sides of tubes of 50x25x2 mm. Between the horizontal tubes palings have been placed.
FRAME SLANTING	The frame can be delivered with a different angle.
PALINGS	Round tubes with a diameter of 26 mm are being used. The centre-to-centre is 150 mm, optional other c/c distances can be delivered.
RINGS	The rings have a diameter of 125 mm and are 6 mm thick.
POINTS BETWEEN PALINGS	Between the palings points can be assembled at the bottom. These points are made out of steel and have a diameter of 16 mm and is approximately 150 mm high. This is an extra protection again climbers.
GROUND ANCHORING	On one side the tail end can be delivered with an extended post or on a base plate. The post is 60 x 60 mm.
CONNECTING FENCING	The posts are being delivered with gauze peak connection. Optional strips of a weld mesh connection can be delivered.
SURFACE TREATMENT	Hot dip galvanised according NEN-EN-ISO 1461.
POWDER COATING	For an appealing and finishing touch an extra RAL coating layer can be put on. This will be done according NEN 5254.

TECHNICAL SPECIFICATIONS

CLASSIC LINE PRO	WIDE	HEIGHT	FRAME	POSTS	PALINGS	C/C PALINGS	POINTS BETWEEN PALINGS Ø 16
CLP10.10	1000	1000	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLP10.12	1000	1250	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLP10.15*	1000	1500	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLP10.18*	1000	1800	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLP10.20*	1000	2000	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD
CLP10.25*	1000	2500	50 x 25 x 2	60 x 60 x 2	Ø 26	150	STANDARD

* STANDARD CUT TO A POINT
ALL SIZES IN MM