



RASTER LINE 6/5/6 (RL656)

This type is lighter than the 8/6/8 – version and can be fixed to the posts in several different ways. The flat panels have double horizontal wires of Ø 6 mm and one vertical wire of Ø 5 mm.

WELDMESH

The weld mesh panels have standard mesh of 200 x 50 mm. Panels can be fixed to the post in many different ways.

POSTS TUBES Ø 60.3

When circular (Ø 60.3) posts are specified, weldmesh panels are mounted centrally between posts. Universal clamps fix the panels to the post.

POSTS TUBES 60/40

Fixing panels to 60 x 40mm rectangular posts is possible using alternative methods:

1. **Type STG:** With use of stainless steel u-clamps.
2. **Type STA:** Posts with full height clamp bar. Plastic shoes @ 200 mm centres including a blind rivet nut and full height clamp bar.
3. **Type STK:** Posts with standard clips. Plastic shoes including a blind rivet nut with steel clips.

BARBED TOP

The weldmesh panel on one edge has barbed tops 30 mm long. This is designed to hinder any attempts to climb up the fence, when placed up. This can be placed down for use where security is less important for example schools and playgrounds.

GROUND ANCHORING

Posts are available with a base plate to give post more stability. Depending on the condition of the soil a (prefab) concrete foot can be supplied to place the post in. Especially useful for “frozen or waterlogged “ ground

SURFACE TREATMENT

Hot dip galvanized according to NEN-EN-ISO 1461.

POWDER COATING

For an appealing and finishing touch an extra coated finish is available. Applied according to NEN 5254.

PRODUCT INFORMATION WELDMESH FENCING PANEL SYSTEM

TECHNICAL SPECIFICATIONS

RASTER LINE 6/5/6	HEIGHT WELDMESH	HEGHT FROM GROUND LEVEL	WIREDIAMETER HORIZONTAL	WIREDIAMETER VERTICAL	MESH	C/C POSTS ROUND Ø 60.3	C/C POSTS 60/40	CONCRETE FOOTING
RL63	630	700	6	5	54 x 200	2580	2510	OPTION
RL83	830	900	6	5	54 x 200	2580	2510	OPTION
RL103	1030	1100	6	5	54 x 200	2580	2510	OPTION
RL123	1230	1300	6	5	54 x 200	2580	2510	OPTION
RL143	1430	1500	6	5	54 x 200	2580	2510	OPTION
RL163	1630	1700	6	5	54 x 200	2580	2510	OPTION
RL183	1830	1900	6	5	54 x 200	2580	2510	OPTION
RL203	2030	2100	6	5	54 x 200	2580	2510	OPTION
RL223	2230	2300	6	5	54 x 200	2580	2510	OPTION
RL243	2430	2500	6	5	54 x 200	2580	2510	OPTION

ALL SIZES ARE IN MM

overview clamps

